



Technical Data Sheet

SUTO 10W-40

Product Description

Semi-synthetic multifunctional oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined and synthetic base oils and additives, to achieve the following properties:

- a powerful dispersion and detergency
- a high activity against wear, corrosion and foam
- a very strong resistance to oxidation
- an excellent extreme pressure properties
- a high and stable viscosity index

Application

This multifunctional lubricant (Super Universal Tractor Oil) has been developed to achieve one single lubricating oil that is able to lubricate:

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions (also "wet" brakes)
- hydraulic systems

Typical Properties

Density at 15 °C, kg/l 0,877	Viscosity 100 °C, mm ² /s 13,60
Viscosity -25 °C, mPa.s 6200	Viscosity Index 153
Viscosity 40 °C, mm ² /s 90,40	Flash Point COC, °C 218
Pour Point, °C -39	Total Base Number, mgKOH/g 11,3

Specifications

API SF/CG-4/GL-4	John Deere J27 / J20C
ACEA E3, MIL-L-2104D	Massey Ferguson CMS M1145 / M1144
Allison C4	Massey Ferguson CMS M1143
Cat TO-2	MB 228.1 / 227.1
Ford M2C159-C / M2C134-D	ZF TE-ML 06B / 07B